



## Chicago Pneumatic CP2012 Screwdrivers - Shut off 2-5 1/2NM

Productivity improved. Ideal for multiple applications. Fast cycle times for productivity. Ideal for centering screws during the fastening cycle. Range: 2 - 5 1/2 Nm 1.475 - 4.056 ft.lbs

| Specifications             | Details                                 |
|----------------------------|-----------------------------------------|
| Model Number               | CP2012                                  |
| Output drive               | 1/4"                                    |
| Sound pressure             | 73 db(A)                                |
| Clutch type                | Shut off                                |
| Min working torque         | Metric: 2 Nm Imperial: 1.475 ft.lbs     |
| Bit holder                 | Quick Change Hexagonal Female           |
| Vibration uncertainty (K)  | - m/s <sup>2</sup>                      |
| Screw type soft            | x                                       |
| Screw type hard            | x                                       |
| Min. Hose Size             | Metric: 10 mm Imperial: 3/8"            |
| Handle Type                | Straight                                |
| Product Number             | 6151922012                              |
| Diameter                   | Metric: 34 mm Imperial: 1.33"           |
| Free speed air consumption | Metric: 9 l/s Imperial: 19.1 cfm        |
| Net weight                 | Metric: 0.9 kg Imperial: 2 lb           |
| Max working torque         | Metric: 5 1/2 Nm Imperial: 4.056 ft.lbs |
| Free Speed                 | 1470 rpm                                |
| Air inlet thread size      | 1/4"                                    |
| Length                     | Metric: 278 mm Imperial: 10.9"          |

| Specifications | Details           |
|----------------|-------------------|
| Brand          | Chicago Pneumatic |
| Vibration ISO  | ISO-28927-2       |

