

Kern FKT 0.02L 6kg Bench scale



80 memories for each operation mode, e.g., for checkweighing, PRE-TARE, reference weight, target weight when dispensing etc. Convenient recipe weighing: 99 recipes each with 10 components each can be stored in plain text. If one recipe ingredient is overweight, then the practical recipe adjustment function for when dosages are exceeded automatically calculates the new target weights of the other ingredients. The actual and target values and the proportionate percentage can then be printed. The recipes can be generated easily in an Excel list at the PC and transferred to the balance using the RS-232 interface. Alternatively, the recipes can also be entered directly using the keypadMultiplier function: recipes where the ingredients have been recorded as percentages can easily be multiplied when entering the new target weight is entered, target weight , which is ideal for the production of larger containers, bulk packs etc. Rapid function for shortened stabilisation time with reduced readout16 print forms which can store up to 20 different information, such as, e.g., date, time, operator, item, net, tare, gross, PCS, target weight, PRE-TARE etc. The print forms can be generated easily in an Excel list in the PC and transferred to the balance using the RS-232 interfaceControl outputs (optocoupler, digital I/O) to connect relays, signal lamps, valves etc. (35 V / 80 mA) Hook for underfloor weighing of hanging loads standard for models with weighing plate size For particularly high counting accuracy, there is an option of combining the KERN FKT range with a high-precision reference balance to make a counting system, please enquireModes Weighing Counting Dispensing Recipe weighing Checkweighing Totalising with daily total Percentage determination Animal weighing Surface weight Density determination, only with , not for Rapid function, not for

Specifications	Details
Warm up time	2 h
Weighing range [Max]	6 kg
Weighing system	Strain gauge
Weighing units	ct dwt g kg lb mo oz ozt t tl (HK) tl (Singap. Malays) tl (Tw)
Maximum humidity	80 %
Maximum operating temperature	40 Å°C
Minimum ambient temperature	10 Å°C
Gross weight	7.6 kgs
Level indicator:	yes
Revolving screw feet:	yes

Specifications	Details
Mains adapter/adapter included:	CH EURO
Operating time (Backlight on):	10 h
Rechargeable battery:	Rchrg. battery optional - intern
Weighing with tolerance range:	yes
Counting function:	yes
Percentage determination	yes
Counting resolution	300000
Minimum piece weight at piece counting (Laboratory)	20 mg
Mininum piece weight at piece counting (Normal)	200 mg
Function to save totals:	yes
PRE-TARE function:	yes
Stabilisation time	3 s
Resolution	300000
Reproducibility	40 mg
Readout [d]	20 mg
Linearity	100 mg
Adjustment options	External calibration
Operating time (Backlight off)	20 h
Standby function:	yes
Operating time	20 h
Input voltage	100 V - 240 V
Charging time	10 h
Display digit height:	4 mm
Weighing surface (WxD):	340 mm x 240 mm
Material weighing plate:	stainless steel

Specifications	Details
Dimensions housing (WxDxH):	350 mm x 390 mm x 120 mm
Net weight	6.5 kgs
Model Number	FKT 0.02L
Brand	Kern
Product Number	FKT 6K 0.02L
Time display:	yes
Suspended weighing	Hook
Reference weight:	yes
Conversion function:	yes
Dispensing function:	yes
SLEEP function:	yes
Statistical function:	yes
Vibration-free weighing (Animal weighing program)	yes
Recommended adjusting weight	5 kg (F1); 1 kg (F1)