

## Norbar PneuTorque PT 2-Automatic Two Speed Pneumatic Torque Multiplier 515-1700NM, Square Size: 3/4"



Pneumatic wrenches from PneuTorque provide a smooth and continuous output drive that may be adjusted with an air pressure regulator (Lubro Control Unit). The tool will stall out with a repeatability of 5% on a specific joint after setting the air pressure from the supplied graph. The direction/shut-off control for remote control versions is provided via external pneumatic circuitry rather than on the tool itself. The PneuTorque now has a wide range of applications, from basic stall shut-off in a dangerous working environment to complicated multi-spindle torque and angle shut-off systems. The PneuTorque operator can run down a nut at 5 times typical operating speed before the Auto Two Speed gearbox automatically switches gear to apply the final torque.

Specifications	Details
Range Imperial	380 - 1250 lbf·ft
Range Metric	515 - 1700 N·m
Max Air Pressure	4.2 bar
Air Consumption	19 litres/sec
Vel Ratio Low Speed	508.019:1
Reac Plate Weight	2.2 Kg
Vel Ratio High Speed	93.137:1
Free Run Low Speed	9 revs/min
Free Run High Speed	45 revs/min
Reac Plate Torque	9 N.m
Model Number	PT 2-Automatic Two Speed
Brand	Norbar
Product Number	16008.XAUT
Tool Weight	14.6 Kg
Accuracy	+/-5%