


UAE Email: mathews@generaltechuae.com Tel : +971 (0) 2 550 7702 Fax : +971 (0) 2 550 7706

SAUDI Mathews@generaltechsaudi.com Tel : +966 (0) 3 834 4264 Fax : +966 3 834 4538



NORBAR HT7/75 1 1/2 MANUAL TORQUE MULTIPLIERS 600-6000NM

Multiple stages of epicyclic gearing are used in Norbar's 'HandTorque' multipliers to provide a wide range of torque outputs and ratios to suit most applications. The torque multiplication ratio is always quoted, not the velocity ratio as some competitors' goods claim. For example, a velocity ratio of 29.8:1 would result in a torque multiplication of 25:14%.

| Specifications | Details |
|----------------------|-------------------|
| Range Imperial | 450 - 4500 lbf·ft |
| Range Metric | 600 - 6000 N·m |
| Max Input Speed | 175 revs/min |
| Plate Torque | 75 N.m |
| Accuracy | +/-4% |
| Tool Weight | 11.1 Kg |
| Plate Weight | 6.3 Kg |
| Product Number | 16068.75 |
| Brand | Norbar |
| Model Number | HT7/75 1 1/2" |
| Multiplication Ratio | 75:1 |
| Output Square | 1 1/2" |
| Input Square | 1/2" |
| Velocity Ratio | 93.137:1 |