

Barton 199N (0 - 100" WC) SWP :2000PSI | Differential Pressure Unit | DP Range: 0-100"WC | SWP: 2000PSI



Differential Pressure Unit with DP Range: 0-100"WC, SWP: 2000PSI

Specifications	Details
Working pressure max	2000PSIG
Housing Material	FORGED STEEL Bellow Material 316 SS
Technical Data	<p>"199N BARTON NACE D P UNIT Application Commercial Model 199N NACE DIFF. PRESS. UNIT Service Nace Safe Working Pressure 2000 PSIG Housing Material FORGED STEEL Bellow Material 316 SS O-Ring VITON Spring Material INCONEL Spring Range 100 "WC (97-107 "WC) Spring Span 0-100"WC Calibration Range Type Standard (0-X) Fill Fluid Hydrocarbon Oil DPU Connection DP CONN: 1/2" NPT TOP X 1/4" N TTType Std (200A,289A,289AS,202E,274) Mounting 2" PIPE SLIP-ON MTG -200A,289A Testing No Special Test Required Customer Tag None Documents Cert of NACE Compliance Cleaning Class III (Standard) Data Plate DPU 199 D Safe Working Pressure 2000 PSIG Diff Pressure Range 100 "WC (97-107 "WC) Calibrated Range 0-100"WC Bellows 316 SS Fill M (Hydrocarbon Oil) "</p>