

Dial Indicators

SERIES 0 - Compact type



1911



1923



1911



1913-10

SPECIFICATIONS

Inch Stem dia. 3/8", #4-48 UNF Thread □ ANS/AGD type

| Graduation | Range | Range/rev | Dial reading | Order No. | | Accuracy | | Measuring force | Jeweled bearing type |
|------------|-------|-----------|--------------|----------------|-----------------|---------------|------------------|-----------------|----------------------|
| | | | | w/ lug | Flat-back | First 2.5 Rev | Overall Accuracy | | |
| .0001" | .01" | .004" | 0-2-0 | 1927-10 | 1927B-10 | ±.0002" | ±.0002" | 1.4N or less | ✓ |
| .0001" | .025" | .01" | 0-5-0 | 1925-10 | 1925B-10 | ±.0002" | ±.0002" | 1.4N or less | ✓ |
| .0005" | .05" | .02" | 0-10-0 | 1923 | 1923B | ±.0005" | ±.0005" | 1.4N or less | — |
| .001" | .1" | .04" | 0-20-0 | 1921 | 1921B | ±.001" | ±.001" | 1.4N or less | — |

Metric Stem ø 8mm, M2.5 x 0.45 Thread □ ISO/JIS type

| Graduation | Range | Range/Rev | Dial reading | Order No. | | Accuracy | | Measuring force | Jeweled bearing type |
|------------|-------|-----------|--------------|----------------|-----------------|---------------|------------------|-----------------|----------------------|
| | | | | w/ lug | Flat-back | First 2.5 Rev | Overall Accuracy | | |
| 0.002mm | 0.5mm | 0.2mm | 0-100-0 | 1913-10 | 1913B-10 | ±0.011mm | ±0.011mm | 1.4N or less | ✓ |
| 0.01mm | 2.5mm | 1mm | 0-50-0 | 1911 | 1911B | ±0.011mm | ±0.011mm | 1.4N or less | — |

□ Jeweled bearing type

DIMENSIONS

Inch Model Unit: Inch

| Order Number | A | B |
|----------------|-------|------|
| 1927-10 | 1.46" | .26" |
| 1925-10 | 1.48" | .28" |
| 1923 | 1.51" | .31" |
| 1921 | 1.58" | .37" |

Metric Model Unit: mm

| Order Number | A | B |
|----------------|------|------|
| 1911 | 42 | 11.5 |
| 1913-10 | 39.5 | 9 |