## **Holtest**

## SERIES 468 – Digimatic Holtest Three-Point Bore Micrometer Interchangeable-Head Sets















468-976 468-977 468-979

## **Specifications**

Incl	ı/M	letr	ic	
шч	1/41/	90		

Code No.	Range	Con	tent of set		
468-976	.2755" (6.985 - 12.7 mm)	Display unit Measuring head  Setting ring  Extension rod Spanner Hex wrench Phillips screw driver	.27535" .35425" .4255" ø.35" ø425" 100 mm	1 pc 1 pc 1 pc 1 pc 1 pc 1 pc 1 pc 2 pcs 1 pc 1 pc	
468-977	.58" (12.7 - 20.32 mm)	Display unit Measuring head Setting ring Extension rod Spanner Hex wrench Phillips screw driver	.565" .658" ø.65" 150 mm	1 pc 1 pc 1 pc 1 pc 1 pc 2 pc 1 pc 1 pc	
468-978	.8 - 2 " (20.32 - 50.8 mm)	Display unit Measuring head Setting ring Extension rod Spanner Hex wrench Phillips screw driver	.8-1" 1-1.2" 1.2-1.6" 1.6-2" Ø1" Ø1.6" 150 mm	1 pc 1 pc 1 pc 1 pc 1 pc 1 pc 1 pc 1 pc	
468-979	2 - 4 " (50.8 - 101.6 mm)	Display unit Measuring head Setting ring Extension rod Spanner Hex wrench Phillips screw driver	2-2.5" 2.5-3" 3-3.5" 3.5-4" ø2.5" ø3.5" 150 mm	1 pc 1 pc 1 pc 1 pc 1 pc 1 pc 1 pc 1 pc	
468-980	4-8" (101.6-203.2 mm)	Display unit Measuring head Setting ring Extension rod Spanner Hex wrench Phillips screw driver	4-5" 5-6" 6-7" 7-8" ø5" ø7" 150 mm	1 pc 1 pc 1 pc 1 pc 1 pc 1 pc 1 pc 1 pc	

Note: It is not advisable to use measuring heads other than those supplied as standard accessories, or attempt to widen a measuring range by using any other heads. (The measuring accuracy in such cases is not guaranteed.)



## **Optional Accessories**

Code No.	Description	
02AZD790B	U-WAVE-T data cable with pushbutton (160 mm)	
02AZE140B	U-WAVE-T data cable with pushbutton and footswitch connection (160/500 mm)	
04AZB157	Mounting bracket	
05CZA662	SPC data cable with pushbutton (1 m)	
05CZA663	SPC data cable with pushbutton (2 m)	
06AFM380B	USB Input Tool Direct USB-ITN-B (2 m)	