


IEC201

IEB3002BBPKG/AM/AS-514-TPS

Inductive sensors



Made in Germany



Product characteristics

Inductive sensor
Metal thread M8 x 1
Connector
Full metal housing
Increased sensing range
Gold-plated contacts
Sensing range 2 mm; [f] flush mountable

Electrical data

Electrical design	DC PNP
Operating voltage [V]	10...36 DC
Current consumption [mA]	< 20
Protection class	III
Reverse polarity protection	yes

Outputs

Output function	normally open
Voltage drop [V]	< 2.5
Leakage current [mA]	< 0.1
Current rating [mA]	100
Short-circuit protection	pulsed
Overload protection	yes
Switching frequency [Hz]	100

Range

Sensing range [mm]	2
Operating distance [mm]	0...1.6

Accuracy / deviations

Correction factors	stainless steel approx. 0.6 / brass approx. 0.4 / Al approx. 0.3 / Cu approx. 0.2
Hysteresis [% of Sr]	1...20

Environment

Pressure rating [bar]	100; *)
Ambient temperature [°C]	-25...70
Protection	IP 67

Tests / approvals

EMC	EN 61000-4-2 ESD:	4 kV CD / 8 kV AD
	EN 61000-4-3 HF radiated:	10 V/m (80...1000 MHz)
	EN 61000-4-4 Burst:	2 kV
	EN 61000-4-6 HF conducted:	10 V (0.15...80 MHz)
	EN 55011:	class B
MTTF [Years]		1989

IEC201

IEB3002BBPKG/AM/AS-514-TPS

Inductive sensors

Mechanical data

Mounting	flush mountable
Housing materials	housing: stainless steel 316L / 1.4404; active face: stainless steel 316L / 1.4404; lock nuts: stainless steel 316L / 1.4404
Weight [kg]	0.018


Displays / operating elements

Output status indication	LED	yellow (4 x 90°)
--------------------------	-----	------------------

Electrical connection

Connection	M8 connector; Gold-plated contacts
------------	------------------------------------

Wiring



Accessories

Accessories (included)	2 lock nuts
------------------------	-------------

Remarks

Remarks	*) sensing face
Pack quantity [piece]	1