


IFC246

IFK3008-BPKG/M/K1/US-104-DPS

Inductive sensors



Made in Germany



Product characteristics

Inductive sensor
Metal thread M12 x 1
Connector
Electromagnetic-field immune
Gold-plated contacts
Correction factor = 1
Sensing range 8 mm; [nf] non-flush mountable

Electrical data

Electrical design	DC PNP
Operating voltage [V]	10...30 DC *)
Current consumption [mA]	20
Protection class	II
Reverse polarity protection	yes

Outputs

Output function	normally open
Voltage drop [V]	< 2.5
Leakage current [mA]	< 0.1
Current rating [mA]	200
Short-circuit protection	pulsed
Overload protection	yes
Switching frequency [Hz]	2000

Range

Sensing range [mm]	8
Real sensing range (Sr) [mm]	8 ± 10 %
Operating distance [mm]	0...6.5

Accuracy / deviations

Correction factors	mild steel = 1 / stainless steel approx. 1 / brass approx. 1 / aluminium approx. 1 / copper approx. 1
Switch-point drift [% of Sr]	-10...10

Environment

Ambient temperature [°C]	-25...70
Protection	IP 68; "Coolant"

Tests / approvals

MTTF [Years]	1978
--------------	------

Mechanical data

Mounting	non-flush mountable
Housing materials	housing: stainless steel (316L); active face: LCP

IFC246

IFK3008-BPKG/M/K1/US-104-DPS

Inductive sensors

Weight [kg] 0.029


Displays / operating elements

Output status indication LED yellow (4 x 90°)

Electrical connection

Connection M12 connector; Gold-plated contacts

Wiring



Accessories

Accessories (included) 2 lock nuts

Remarks

Remarks *) cULus - Class 2 source required

Pack quantity [piece] 1